

TECHNICAL DATA SHEET

| | |
|----------------|-------------------------|
| QUALITY | BONDFOAM |
| SIZE | 2070x1030x100 mm |

| Description | Standard | Value | Unit |
|--|---|---------------------|-------------------|
| Density (gross) | ISO 845 | 180 | Kg/m ³ |
| Compression 25% Tolerance +/- 10% | ISO 2439 | 1153 | N |
| Compression 40% Tolerance +/- 10% | ISO 2439 | 2703 | N |
| Compression 65% Tolerance +/- 12,5% | ISO 2439 | 11929 | N |
| Tensile strength (Min) | ISO 1798 | 77,2 | Kpa |
| Elongation at break (Min) | ISO 3386 | 58 | % |
| Tear resistance | ISO 3386 | 264 | Kpa |
| Fire resistance | NFT 56 125 D 45 1333 FMVSS 302 NF P 92-504 | D E Yes M4 | |
| Recyclability | | 100 | % |

The values provided in this product information represent data gathered from random samples of our production and represent typical data. These are given to the best of our knowledge and should be considered as guidance for selecting a suitable grade for a given application.

This information is presented to the best of our knowledge. Data represents typical values and should be considered as a guideline only.

Where this material is used in conjunction with other goods or materials, it is the responsibility of the user to obtain the manufacturers or suppliers of the other goods or materials all technical data and other properties relating to those other goods or materials. No liability can be accepted in respect of the use of goods or materials in conjunction with any other goods or materials.

Last update: 09/08/2021