

TECHNICAL DATA SHEET

QUALITY	PU AS
COLOUR	Pink

The quality PU AS is an open cell polyurethane foam with an antistatic characteristic.

Description	Standard	Value	Unit
Density (gross)	NF EN ISO 845	20	Kg/m ³ (+/- 1 kg)
Density (net)		18	Kg/m ³ (+/- 1 kg)
Compression 25% Tolerance +/- 15%	NF EN ISO 3386-1	2,6	
Compression 40% Tolerance +/- 15%	NF EN ISO 3386-1	3,0	
Compression 65% Tolerance +/- 15%	NF EN ISO 3386-1	5,2	
Tensile strength (Min)	NF EN ISO 1798	90	Kpa
Elongation at break (Min)	NF EN ISO 1798	110	%
Tear resistance	NF EN ISO 8067	285	N/m

The values provided in this product information represent data gathered from random samples of our production and represent typical data. These are given to the best of our knowledge and should be considered as guidance for selecting a suitable grade for a given application.

This information is presented to the best of our knowledge. Data represents typical values and should be considered as a guideline only.

Where this material is used in conjunction with other goods or materials, it is the responsibility of the user to obtain the manufacturers or suppliers of the other goods or materials all technical data and other properties relating to those other goods or materials. No liability can be accepted in respect of the use of goods or materials in conjunction with any other goods or materials.

Last update: 09/08/2021