

TECHNICAL DATA SHEET

| | |
|----------------|--------------|
| QUALITY | PU AS |
| COLOUR | Pink |

The quality PU AS is an open cell polyurethane foam with an antistatic characteristic.

| Description | Standard | Value | Unit |
|---------------------------|-----------------|------------------|------------------------------|
| Density (gross) | | 21 | Kg/m ³ (+/- 1 kg) |
| Density (net) | DIN EN ISO 845 | 19 | Kg/m ³ (+/- 1 kg) |
| Compression | DIN EN ISO 3386 | 4.0 | KPa |
| Loss of hardness | DIN EN ISO 3385 | 35 | % (Max) |
| Tensile strength (Min) | DIN ISO 1798 | 100 | KPa (Min) |
| Elongation at break (Min) | DIN ISO 1798 | 90 | % (Min) |
| Compression Set | DIN ISO 1798 | 5.5 | % (Max) |
| Electrical resistance | DIN EN 61340 | 10 ¹⁰ | Ω |

No CFCs or solvents are used in the production of our polyurethane foams.

The values provided in this product information represent data gathered from random samples of our production and represent typical data. These are given to the best of our knowledge and should be considered as guidance for selecting a suitable grade for a given application.

This information is presented to the best of our knowledge. Data represents typical values and should be considered as a guideline only.

Where this material is used in conjunction with other goods or materials, it is the responsibility of the user to obtain the manufacturers or suppliers of the other goods or materials all technical data and other properties relating to those other goods or materials. No liability can be accepted in respect of the use of goods or materials in conjunction with any other goods or materials.

Last update: 01/01/2023